

1. A modulator/demodulator system comprising:  
a transmission system which applies one of a plurality of time  
5 scales and one of a plurality of time delays to one of a pair of substantially  
matched base signals, combines the time scaled and time delayed base signal with  
the other one of the pair of base signals to form a doublet, and transmits the  
doublet; and  
a receiving system which receives the doublet and extracts  
10 information from the doublet based on the one of the plurality of time scales and  
the one of the plurality of time delays which were applied.
2. The system as set forth in claim 1 wherein the transmission system  
further comprises:  
15 a signal generator which generates the pair of substantially  
matched base signals;  
an encoding system which modulates the one of the plurality of  
time scales and the one of the plurality of time delays onto the one of the pair of  
substantially matched base signals;  
20 a combiner which combines the time scaled and time delayed base  
signal with the other one of the pair of base signals to form the doublet; and  
a transmitter which transmits the doublet.
3. The system as set forth in claim 1 wherein the transmission system  
25 has a plurality of doublets with an independent one of a plurality of the time scales  
and independent one of the plurality of time delays applied to each of the  
doublets, the transmission system combines all of the doublets to form and  
transmit a composite signal; and  
wherein the receiving system receives the composite signal and  
30 extracts the information from each of the doublets that comprise the composite  
signal based on the respective one of the plurality of time scale and the one of the  
plurality of time delay that were applied to each of the doublets.

4. The system as set forth in claim 2 wherein the transmission system further comprises a pair of synchronized and spatially separated radiating elements, one radiating element radiates one of the substantially matched base signals and the other radiating element radiates the time scaled and time delayed base signal; and

wherein the receiving system further comprises a device that time scales a received signal by the time scale that was applied by the transmission system to form a time scaled version of the received signal, a correlator that correlates the received signal with the time scaled version of the received signal to form a time delay correlation signal, a detector that detects the peaks of this time delay offset correlation signal, and an estimator that uses the time delay offset locations of the peaks to estimate the angle of arrival of each of the received signals.

15

5. The system as set forth in claim 1 wherein the at least one of the pair of substantially matched base signals contains the information and the receiving system extracts the information from the at least one of the pair of substantially matched base signals in the doublet.

20

6. The system as set forth in claim 2 wherein the combiner is an adder or a subtractor.

7. The system as set forth in claim 1 wherein the transmission system further comprises:

25

a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signal; and

a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

30

109765712.011901  
Cat.

9. The system as set forth in claim 1 wherein the information  
5 comprises imaging data embedded by an environment in which the doublet was  
transmitted.

10 a segmentation device that receives the doublet and forms received  
segments from the received doublet;

15 a time delaying device which applies at least one of the plurality of time delays to each of the received segments to form time delayed signal segments;

20 an integrator which integrates the multiplied signals across time to  
form detection signals; and

a processing system which compares the detection signals at different ones of the plurality of time scales and different ones of the plurality of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the information from the detection signal.

30 a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals; and

a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

5           12.    A modulation/demodulation method comprising:  
              applying one of a plurality of time scales and one of a plurality of  
time delays to one of a pair of substantially matched base signals;  
              combining the time scaled and time delayed base signal with the  
other one of the pair of base signals to form a doublet;  
10           transmitting the doublet into the environment;  
              receiving the doublet; and  
              extracting information from the doublet based on the one of the  
plurality of time scales and on the one of the plurality of time delays which were  
applied.

15           13.    The method as set forth in claim 12 further comprising:  
              radiating one of the substantially matched base signals from one of  
a pair of synchronized and spatially separated radiating elements;  
              radiating the time scaled and time delayed base signal from another  
20           one of the pair of synchronized and spatially separated radiating elements;  
              time scaling a received signal by the time scale that was applied to  
form a time scaled version of the received signal;  
              correlating the received signal with the time scaled version of the  
received signal to form a time delay correlation signal;  
25           detecting the peaks of this time delay correlation signal; and  
              using the time delay locations of the peaks to estimate the angle of  
arrival of each of the received signals.

30           14.    The method as set forth in claim 12 further comprising providing a  
plurality of doublets with each of the doublets having an independent one of the  
plurality of time scales and an independent one of the plurality of time delays  
applied to each of the doublets, combining all of the doublets to form a composite  
signal transmitting the composite signal into the environment, receiving the

09462712 "011911  
T06T0 "2160  
ent.

composite signal, and extracting the information from the doublets that comprise the composite signal based on the respective one of the plurality of time scales and one of the plurality of time delays which were applied to each of the doublets.

5           15.     The method as set forth in claim 12 further comprising imbedding information in one of the pair of substantially matched base signals in the doublet.

10           16.     The method as set forth in claim 12 wherein the combining comprises adding or subtracting the time scaled and time delayed base signal with the other one of the pair of base signals to form the doublet.

15           17.     The method as set forth in claim 12 further comprising:  
                    substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals prior to the transmitting; and  
                    substantially assuring that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals prior to the transmitting.

20           18.     The method as set forth in claim 12 wherein the information comprises a message embedded prior to the transmission of the doublet.

25           19.     The method as set forth in claim 12 wherein the information comprises imaging data embedded by an environment in which the doublet was transmitted.

30           20.     The method as set forth in claim 12 wherein the receiving further comprises:  
                    segmenting the received doublet to form received segments;  
                    applying at least one of the plurality of time scales to each of the received segments to form time scaled signal segments;

106765712-011901

applying at least one of the plurality of time delays to each of the received segments to form time delayed signal segments;

multiplying each of the time scaled signal segments with each of the time delayed signal segments to form multiplied signals;

5 integrating the multiplied signals across time to form detection signals; and

processing the detection signals at different ones of the plurality of time scales and different ones of the plurality of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the information from the determined detection signal.

21. The method as set forth in claim 20 further comprising:  
substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals following the receiving; and  
substantially assuring that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals following the receiving.

22. A modulation/demodulation system comprising:  
a transmission system which applies one of a plurality of time scales to one of a pair of substantially matched base signals, combines the time scaled base signal with the other one of the pair of base signals to form a doublet, and transmits the doublet; and  
a receiving system which receives the doublet and extracts information from the doublet based on the one of the plurality of time scales which was applied.

23. The system as set forth in claim 22 wherein the transmission system further comprises a pair of synchronized and spatially separated radiating elements, one radiating element radiates one of the substantially matched base signals and the other radiating element radiates the time scaled base signal; and

09765712.011901  
A1 Cont.

10 a transmitter which transmits the doublet.

wherein the receiving system receives the composite signal and extracts the information from each of the doublets that comprise the composite signal based on the respective time scales applied to each of the doublets.

20            26.     The system as set forth in claim 23 wherein the combiner is an  
addor or a subtractor.

30 a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

28. The system as set forth in claim 22 wherein the information comprises a message embedded by the transmission system.

29. The system as set forth in claim 22 wherein the information comprises imaging data embedded by an environment in which the doublet was transmitted.

5

30. The system as set forth in claim 22 wherein the receiving system further comprises:

a segmentation device that receives the doublet and forms received segments from the received doublet;

10 a time scaling device which applies at least one of the plurality of time scales to each of the received segments to form time scaled signal segments; and

A  
09/05/12 01:50  
a processing system which compares the time scaled signal segments at different ones of the plurality of time scales over time to determine  
15 the applied one of the plurality of time scales to extract the information from the detection signal.

31. The system as set forth in claim 22 wherein at least one of the pair of substantially matched base signals contains the information and the receiving  
20 system extracts the information from the one of the pair of substantially matched base signal in the doublet with the information..

32. A modulation/demodulation method comprising:  
applying one of a plurality of time scales to one of a pair of  
25 substantially matched base signals;  
combining the time scaled base signal with the other one of the pair of base signals to form a doublet;  
transmitting the doublet into the environment;  
receiving the doublet; and  
30 extracting information from the doublet based on the one of the plurality of time scales which was applied.

33. The method as set forth in claim 32 further comprising further  
comprising providing a plurality of doublets with each of the doublets having an  
independent one of the plurality of time scales, combining all of the doublets to  
form a composite signal, transmitting the composite signal into the environment,  
5 receiving the composite signal, and extracting the information from the doublets  
that comprise the composite signal based on the respective one of the plurality of  
time scales applied to each of the doublets.

34. The method as set forth in claim 32 further comprising extracting  
10 the information from the one of the pair of substantially matched base signals in  
the doublet.

35. The method as set forth in claim 32 wherein the combining  
comprises adding the time scaled base signal with the other one of the pair of base  
15 signals to form the doublet.

36. The method as set forth in claim 32 wherein the combining  
comprises subtracting the time scaled base signal with the other one of the pair of  
base signals to form the doublet.

37. The method as set forth in claim 32 further comprising:  
substantially assuring that signal energy of the pair of substantially  
matched base signals is evenly distributed across the duration of the pair of  
substantially matched base signals prior to the transmitting; and  
25 substantially assuring that the signal energy is evenly distributed  
across the spectrum of the pair of substantially matched base signals prior to the  
transmitting.

38. The method as set forth in claim 32 wherein the information  
30 comprises a message embedded prior to the transmission of the doublet.

03705712 "011901  
T0611901

39. The method as set forth in claim 38 wherein the information comprises imaging data embedded by an environment in which the doublet was transmitted.

5 40. The method as set forth in claim 32 wherein the receiving further comprises:

segmenting the received doublet to form received segments;  
applying at least one of the plurality of time scales to each of the  
received segments to form time scaled signal segments; and  
10 processing the time scaled signal segments at different ones of the plurality of time scales over time to determine the applied one of the plurality of time scales to extract the information from the determined time scaled signal segments signal.

15 41. The method as set forth in claim 32 further comprising:

substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals following the receiving; and  
substantially assuring that the signal energy is evenly distributed  
20 across the spectrum of the pair of substantially matched base signals following the receiving.

42. A transmission system for transmitting information comprising:  
an encoding system which applies one of a plurality of time scales  
25 to one of a pair of substantially matched base signals;  
a combiner which combines the time scaled base signal with the other one of the pair of base signals to form a doublet; and  
a transmitter which transmits the doublet with the information.

30 43. The system as set forth in claim 42 wherein the encoding system has a plurality of doublets with an independent one of the plurality of time scales applied to each of the doublets, the combiner combines all of the doublets to form a composite signal, and transmits the composite signal;

10755712-011901

44. The system as set forth in claim 42 wherein the transmission system further comprises a signal generator which generates the pair of substantially matched base signals and the encoding system comprises a first  
5 encoder which modulates the one of the plurality of time scales onto the one of the pair of substantially matched base signals and a second encoder which modulates the one of the plurality of time delays onto the one of the pair of substantially matched base signals.

10 45. The system as set forth in claim 42 wherein the combiner is an adder.

46. The system as set forth in claim 42 wherein the combiner is a subtractor.

15 47. The system as set forth in claim 42 further comprising:  
a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signal; and  
20 a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

25 48. A method for transmitting information comprising:  
applying one of a plurality of time scales to one of a pair of substantially matched base signals;  
combining the time scaled with the other one of the pair of base signals to form a doublet with the information; and  
transmitting the doublet.

30 49. The method as set forth in claim 48 further comprising:  
radiating one of the substantially matched base signals from one of a pair of synchronized and spatially separated radiating elements; and

05765712.011901

radiating the time scaled and time delayed base signal from another one of the pair of synchronized and spatially separated radiating elements.

50. The method as set forth in claim 48 further comprising providing a plurality of doublets with each of the doublets having an independent one of the plurality of time scales, combining all of the doublets to form a composite signal, and transmitting the composite signal into the environment.

51. The method as set forth in claim 48 further comprising applying one of a plurality of time delays to the one of the pair of substantially matched base signals.

52. The method as set forth in claim 48 further comprising imbedding the information in one of the pair of substantially matched base signals in the doublet.

53. The method as set forth in claim 48 wherein the combining comprises adding or subtracting the time scaled base signal with the other one of the pair of base signals to form the doublet.

54. The method as set forth in claim 48 further comprising:  
substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals prior to the transmitting; and  
substantially assuring that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals prior to the transmitting.

55. A receiver system for receiving transmitted information comprising:  
a receiver which receives a doublet; and

Pat. 5,765,121, 01.19.01

a processing system which extracts the information from the doublet based on one of a plurality of time scales which was applied to the doublet prior to transmission.

5           56.    The system as set forth in claim 55 wherein the receiver further comprises a device that time scales a received signal from the doublet by the time scale that was applied to form a time scaled version of the received signal, a correlator that correlates the received signal with the time scaled version of the received signal to form a time delay correlation signal, a detector that detects the  
10    peaks of this time delay correlation signal, and an estimator that uses the time delay locations of the peaks to estimate the angle of arrival of each of the received signals.

          57.    The receiver system as set forth in claim 55 wherein the receiver  
15    receives a plurality of the doublets in a composite signal and the processing system extracts the information from the composite signal based on the one of the plurality of time scales which was applied to each of the doublets.

          58.    The system as set forth in claim 55 wherein the processing system  
20    also extracts the information from the doublet based on one of a plurality of time delays which was applied to the doublet prior to transmission.

          59.    The system as set forth in claim 55 wherein the processing system further comprises:  
25               a segmentation device that receives the doublet and forms received segments from the received doublet;  
              a time scaling device which applies at least one of the plurality of time scales to each of the received segments to form time scaled signal segments;  
              a time delaying device which applies at least one of the plurality of  
30    time delays to each of the received segments to form time delayed signal segments;

100765712 011901

an integrator which integrates the multiplied signals across time to form detection signals, the processing system comparing the detection signals at different ones of the plurality of time scales and different ones of the plurality of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the information from the detection signal.

a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals; and

61. A receiving method for receiving information comprising:  
receiving a doublet; and  
extracting information from the doublet based on one of a plurality  
of time scales which was applied to the doublet.

62. The method as set forth in claim 61 further comprising receiving a plurality of the doublets contained in a composite signal and extracting information from the composite signal based on the one of the plurality of time scales which was applied to each of the doublets.

63. The method as set forth in claim 61 wherein the extraction is also based on one of a plurality of time delays which was applied to the doublet.

64. The method as set forth in claim 61 wherein the information comprises a message embedded prior to the transmission of the doublet.

65. The method as set forth in claim 61 wherein the information comprises imaging data embedded by an environment in which the doublet was transmitted.

66. The method as set forth in claim 61 wherein the extracting further comprises:

10 segmenting the received doublet to form received segments;  
applying at least one of the plurality of time scales to each of the received segments to form time scaled signal segments;  
applying at least one of the plurality of time delays to each of the received segments to form time delayed signal segments;  
15 multiplying each of the time scaled signal segments with each of the time delayed signal segments to form multiplied signals; and  
integrating the multiplied signals across time to form detection signals, wherein the extracting further comprises processing the detection signals at different ones of the plurality of time scales and different ones of the plurality  
20 of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the information from the determined detection signal.

67. The method as set forth in claim 61 further comprising:  
25 substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals following the receiving; and  
substantially assuring that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals following the  
30 receiving.

Al  
00765742-011601  
T06T10"2725940

68. The method as set forth in claim 61 further comprising extracting the information from the one of the pair of substantially matched base signals in the doublet.

5 69. A communication system comprising:  
a transmission system embeds communication information by applying one of a plurality of time scales and one of a plurality of time delays to one of a pair of substantially matched base signals, combines the time scaled and time delayed base signal with the other one of the pair of base signals to form a  
10 doublet, and transmits the doublet; and

a receiving system which receives the doublet and extracts information from the doublet based on the one of the plurality of time scales and the one of the plurality of time delays which were applied.

15 70. The system as set forth in claim 69 wherein the transmission system further comprises:

a signal generator which generates the pair of substantially matched base signals;

20 an encoding system embeds the communication information by modulating the one of the plurality of time scales and the one of the plurality of time delays onto the one of the pair of substantially matched base signals;

a combiner which combines the time scaled and time delayed base signal with the other one of the pair of base signals to form the doublet; and

a transmitter which transmits the doublet.

25

71. The system as set forth in claim 69 wherein the transmission system has a plurality of doublets with an independent one of a plurality of the time scales and independent one of the plurality of time delays applied to each of the doublets, the transmission system combines all of the doublets to form and  
30 transmit a composite signal; and

wherein the receiving system receives the composite signal and extracts the information from each of the doublets that comprise the composite

7/10/95 7:12 PM  
T067701

signal based on the respective one of the plurality of time scale and the one of the plurality of time delay that were applied to each of the doublets.

72. The system as set forth in claim 69 wherein the at least one of the pair of substantially matched base signals contains additional information and the receiving system extracts the additional information from the at least one of the pair of substantially matched base signals in the doublet with the additional information.

73. The system as set forth in claim 70 wherein the combiner is an adder or a subtractor.

74. The system as set forth in claim 69 wherein the transmission system further comprises:  
a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signal; and  
a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

75. The system as set forth in claim 69 wherein the receiving system further comprises:  
a segmentation device that receives the doublet and forms received segments from the received doublet;  
a time scaling device which applies at least one of the plurality of time scales to each of the received segments to form time scaled signal segments;  
a time delaying device which applies at least one of the plurality of time delays to each of the received segments to form time delayed signal segments;  
a multiplier which multiplies each of the time scaled signal segments with each of the time delayed signal segments to form multiplied signals;

an integrator which integrates the multiplied signals across time to form detection signals; and

5 a processing system which compares the detection signals at different ones of the plurality of time scales and different ones of the plurality of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the communication information from the detection signal.

10 76. The system as set forth in claim 75 wherein the receiving system further comprises:

a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals; and

15 a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

77. A method for communicating comprising:

20 applying one of a plurality of time scales and one of a plurality of time delays to one of a pair of substantially matched base signals to embed communication information;

combining the time scaled and time delayed base signal with the other one of the pair of base signals to form a doublet;

25 transmitting the doublet into the environment;  
receiving the doublet; and

extracting the communication information from the doublet based on the one of the plurality of time scales and on the one of the plurality of time delays which were applied.

30 78. The method as set forth in claim 77 further comprising providing a plurality of doublets with each of the doublets having an independent one of the plurality of time scales and an independent one of the plurality of time delays applied to each of the doublets to embed the communication information,

Al. 712.011901

5

10

15

20

25

30

multiplying each of the time scaled signal segments with each of the time delayed signal segments to form multiplied signals;

integrating the multiplied signals across time to form detection signals; and

processing the detection signals at different ones of the plurality of time scales and different ones of the plurality of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the communication information from the determined detection signal.

83. The method as set forth in claim 82 further comprising:  
substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals following the receiving; and  
substantially assuring that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals following the receiving.

84. An imaging system comprising:  
a transmission system which applies one of a plurality of time scales and one of a plurality of time delays to one of a pair of substantially matched base signals, combines the time scaled and time delayed base signal with the other one of the pair of base signals to form a doublet, and transmits the doublet into an environment which embeds imaging information in the doublet; and  
a receiving system which receives the doublet and extracts the imaging information from the doublet based on the one of the plurality of time scales and the one of the plurality of time delays which were applied.

85. The system as set forth in claim 84 wherein the transmission system further comprises:  
a signal generator which generates the pair of substantially matched base signals;  
an encoding system which modulates the one of the plurality of time scales and the one of the plurality of time delays onto the one of the pair of substantially matched base signals;

a combiner which combines the time scaled and time delayed base signal with the other one of the pair of base signals to form the doublet; and  
a transmitter which transmits the doublet into the environment which embeds the imaging information.

5

86. The system as set forth in claim 84 wherein the transmission system has a plurality of doublets with an independent one of a plurality of the time scale and independent one of the plurality of time delay applied to each of the doublets, combines all of the doublets to form a composite signal, and  
10 transmits the composite signal; and

wherein the receiving system receives the composite signal and extracts the information from each of the doublets that comprise the composite signal based on the respective one of the plurality of time scale and the one of the plurality of time delay that were applied to each of the doublets.

15

87. The system as set forth in claim 85 wherein the transmission system further comprises a pair of synchronized and spatially separated radiating elements, one radiating element radiates one of the substantially matched base signals and the other radiating element radiates the time scaled and time delayed  
20 base signal into the environment which embeds the imaging information; and

wherein the receiving system further comprises a device that time scales a received signal by the time scale that was applied by the transmission system to form a time scaled version of the received signal, a correlator that correlates the received signal with the time scaled version of the received signal to  
25 form a time delay correlation signal, a detector that detects the peaks of this time delay offset correlation signal, and an estimator that uses the time delay offset locations of the peaks to estimate the angle of arrival of each of the received signals.

30

88. The system as set forth in claim 85 wherein the combiner is an adder or a subtractor.

105785712.011901

89. The system as set forth in claim 84 wherein the transmission system further comprises:

- a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signal; and
- a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

90. The system as set forth in claim 84 wherein the receiving system further comprises:

- a segmentation device that receives the doublet and forms received segments from the received doublet;
- a time scaling device which applies at least one of the plurality of time scales to each of the received segments to form time scaled signal segments;
- a time delaying device which applies at least one of the plurality of time delays to each of the received segments to form time delayed signal segments;
- a multiplier which multiplies each of the time scaled signal segments with each of the time delayed signal segments to form multiplied signals;
- an integrator which integrates the multiplied signals across time to form detection signals; and
- a processing system which compares the detection signals at different ones of the plurality of time scales and different ones of the plurality of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the imaging information from the detection signals.

91. The system as set forth in claim 90 wherein the receiving system further comprises:

100-5710-011901

a temporal equalizer which substantially assures that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals; and

5 a spectral equalizer which substantially assures that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals.

92. A method for imaging comprising: -  
applying one of a plurality of time scales and one of a plurality of  
10 time delays to one of a pair of substantially matched base signals;

combining the time scaled and time delayed base signal with the other one of the pair of base signals to form a doublet;

transmitting the doublet into the environment that embeds the  
15 imaging information;

receiving the doublet; and  
extracting the imaging information from the doublet based on the  
one of the plurality of time scales and on the one of the plurality of time delays  
which were applied.

20 93. The method as set forth in claim 92 further comprising:  
radiating one of the substantially matched base signals from one of  
a pair of synchronized and spatially separated radiating elements;

radiating the time scaled and time delayed base signal from another  
one of the pair of synchronized and spatially separated radiating elements;

25 time scaling a received signal by the time scale that was applied to  
form a time scaled version of the received signal;

correlating the received signal with the time scaled version of the  
received signal to form a time delay correlation signal;

30 detecting the peaks of this time delay correlation signal; and  
using the time delay locations of the peaks to estimate the angle of  
arrival of each of the received signals.

100765712.011901  
Conti

94. The method as set forth in claim 93 further comprising providing a plurality of doublets with each of the doublets having an independent one of the plurality of time scales and an independent one of the plurality of time delays applied to each of the doublets, combining all of the doublets to form a composite signal, transmitting the composite signal into the environment which embeds the imaging information, receiving the composite signal, and extracting the imaging information from the doublets that comprise the composite signal based on the respective one of the plurality of time scales and one of the plurality of time delays which were applied to each of the doublets.

10

95. The method as set forth in claim 92 wherein the combining comprises adding or subtracting the time scaled and time delayed base signal with the other one of the pair of base signals to form the doublet.

15

96. The method as set forth in claim 92 further comprising:  
substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of substantially matched base signals prior to the transmitting; and  
substantially assuring that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals prior to the transmitting.

20

97. The method as set forth in claim 92 wherein the receiving further comprises:

25

segmenting the received doublet to form received segments;  
applying at least one of the plurality of time scales to each of the received segments to form time scaled signal segments;

applying at least one of the plurality of time delays to each of the received segments to form time delayed signal segments;

30

multiplying each of the time scaled signal segments with each of the time delayed signal segments to form multiplied signals;

integrating the multiplied signals across time to form detection signals; and

5 processing the detection signals at different ones of the plurality of time scales and different ones of the plurality of time delays over time to determine the applied one of the plurality of time scales and the applied one of the plurality of time delays to extract the imaging information from the determined detection signal.

98. The method as set forth in claim 97 further comprising:  
substantially assuring that signal energy of the pair of substantially matched base signals is evenly distributed across the duration of the pair of
- 10 substantially matched base signals following the receiving; and  
substantially assuring that the signal energy is evenly distributed across the spectrum of the pair of substantially matched base signals following the receiving.

09765712 011901